

## BE55050 Hunting Series 2.5-10x50 Telescopic Sight



### DESCRIPTION

The Bering Optics Hunting Series sights are built with high quality optics that provide sharp and high resolution viewing in various conditions. The green-tinted, fully multi-coated optics allows the improved light transmission, achieving a brighter, clearer image in the sunset or sunrise environments.

The scope body is a 30mm in diameter mono-tube that is milled from one solid piece of aircraft aluminum and has a matte black finish to prevent undesirable reflections.

The 2.5-10x50 Telescopic sight features classic German #4 type with switchable red-green illuminated central dot and five brightness settings of each color. There is a non-illuminated black central dot in the "off" position.

### FEATURES

- Shockproof, Waterproof, Fog proof
- Nitrogen gas purged and O-ring sealed
- Fully multicoated optics
- High light transmission coefficient
- Solid one piece d30mm tube construction made of aircraft grade aluminum alloy
- Precise reticle adjustment mechanism
- Quick focus eyepiece
- Finger adjustable windage & elevation
- Turrets with adjustable zero settings
- Central dot LED illuminated reticle with switchable dot color, red or green
- 5 brightness settings for each color

### IN THE BOX

1. 2.5-10x50 Telescopic sight (BE55050)
2. Two flip-up protective caps
3. Lens cleaning tissue
4. CR2032 (3V) coin-style battery
5. Instruction manual

## SPECIFICATIONS

<b>SKU</b>	<b>BE55050</b>
<b>Scope Color</b>	Matt black
<b>Magnification, x</b>	2.5 – 10
<b>Objective lens diameter, mm</b>	50
<b>FOV at a distance 100m, <u>yard</u> / m</b>	13 - 3
<b>Eye relief distance, max., mm</b>	96
<b>Diopter adjustment, D</b>	±2
<b>Exit pupil, mm</b>	20 - 5
<b>Focus range, approx., <u>yard</u> / m</b>	<u>7.2 - 36</u> / 6.5 - 33 to infinity
<b>Reticle type</b>	German #4 type with switchable red-green illuminated central dot
<b>Reticle windage / elevation adjustment range</b>	± 30 MIL
<b>Adjustment knob click value</b>	1/10MIL (¼ MOA) per click
<b>Lens hood diameter, mm</b>	<u>2.34</u> / 59.5
<b>Length, <u>inch</u> / mm</b>	324
<b>Weight with lens covers and battery, <u>oz</u> / g</b>	<u>23.4</u> / 662
<b>Power supply</b>	CR2032 or DL2032 or ECR2032 3V battery (one)
<b>Estimated battery life, hour</b>	400
<b>Water intrusion</b>	Waterproof
<b>Operating temperature, <u>°F</u> / °C</b>	<u>-22 to +122</u> / -30 to +50