

BE55450 Hunting Series 6-24x50 Telescopic Sight



DESCRIPTION

The Bering Optics Hunting Series sights are built with high quality optics that provide sharp and high resolution viewing in various conditions. The green-tinted, fully multi-coated optics allows the improved light transmission, achieving a brighter, clearer image in the sunset or sunrise environments.

The scope body is a 30mm in diameter mono-tube that is milled from one solid piece of aircraft aluminum and has a matte black finish to prevent undesirable reflections.

The scope features classic German #4 type with switchable red-green illuminated central dot and five brightness settings of each color. There is a non-illuminated black central dot in the "off" position.

The distinct feature of the 6-24x50 Hunting Sight is a side focus parallax adjustment mechanism that allows parallax correction from 8 yards (7m) to infinity.

FEATURES

- Shockproof, Waterproof, Fog proof
- Nitrogen gas purged and O-ring sealed
- Side focus parallax correction
- Fully multicoated optics
- High light transmission coefficient
- Solid one piece d30mm tube construction made of aircraft grade aluminum alloy
- Precise reticle adjustment mechanism
- Quick focus eyepiece
- Finger adjustable windage & elevation
- Turrets with adjustable zero settings
- Central dot LED illuminated reticle with switchable dot color, red or green
- 5 brightness settings for each color

IN THE BOX

1. 6-24x50 Telescopic sight (BE55450)
2. Two flip-up protective caps
3. Lens cleaning tissue
4. CR2032 (3V) coin-style battery
5. Instruction manual

SPECIFICATIONS

SKU	BE55450
Scope Color	Matt black
Magnification, x	6 - 24
Objective lens diameter, mm	50
FOV at a distance 100m, <u>yard</u> / m	<u>5.5</u> - 1.64 / 5 - 1.5
Eye relief distance, max., mm	100
Diopter adjustment, D	±2
Exit pupil, mm	8.3 - 2.1
Focus range, approx., <u>yard</u> / m	<u>8</u> - 10 / 7 - 9 to infinity
Reticle type	German #4 type with switchable red-green illuminated central dot
Reticle windage / elevation adjustment range	± 30 MIL
Adjustment knob click value	1/10MIL (¼ MOA) per click
Lens hood diameter, mm	<u>2.34"</u> / 59.5
Length, <u>inch</u> / mm	<u>15"</u> / 380
Weight with lens covers and battery, <u>oz</u> / g	<u>27.4</u> / 776
Power supply	CR2032 or DL2032 or ECR2032 3V battery (one)
Estimated battery life, hour	400
Water intrusion	Waterproof
Operating temperature, <u>°F</u> / °C	<u>-22 to +122</u> / -30 to +50